# भारतीय प्रौद्योगिकी संस्थान, गोवा गोवा अभियांत्रिकी महाविद्यालय परिसर, फारमागुडी, फोण्डा - ४०३४०१, गोवा Indian Institute of Technology Goa



Goa College of Engineering Campus, Farmagudi, Ponda - 403401, Goa

Date: 19/02/2021

# INVITATION OF BIDS FOR NON-DESTRUCTIVE TESTING EQUIPMENT ENQUIRY NO: IITGOA/2020-21/028 DTD 19/02/2021

- 1. Quotations are invited in two bid system for the procurement of Non-Destructive Testing Equipment in separate envelopes. Please mention the above-mentioned title, enquiry number and due date for submission of bids on the sealed cover to avoid the bid being declared invalid.
- 2. The address and contact numbers for sending bids or seeking clarifications regarding this RFP are given below –

Assistant Registrar (Stores & Purchase) IIT GOA, At GEC Campus, Farmagudi, Ponda – Goa. 403401

ar\_sp@iitgoa.ac.in

- 3. This bid enquiry is divided into three parts as follows:
  - a. Part I Contains General Information such as the time, place of submission and opening of tenders, Validity period of tenders, etc.
  - b. Part II Contains Instructions for the Bidders and essential details of the items/services required, such as the Schedule of Requirements (SOR), Technical Specifications, Delivery Period, Place of Delivery and Consignee details.
  - c. Part III Contains Price Bid format, other details etc.
  - 4. This bid enquiry is being issued with no financial commitment and the Institute reserves the right to change or vary any part thereof at any stage and to withdraw it at any stage.

# भारतीय प्रौद्योगिकी संस्थान, गोवा गोवा अभियांत्रिकी महाविद्यालय परिसर, फारमागुडी, फोण्डा - ४०३४०१, गोवा Indian Institute of Technology Goa



Goa College of Engineering Campus, Farmagudi, Ponda - 403401, Goa

### Part I - General information

Tender No.		IITGOA/2020-21/028		
Tender Date		19.02.2021		
Tender Category	,	Goods		
Tender Type		Open		
No. of Envelopes	5	2		
Covers Informati	on / Submission of	Bids		
Cover No.	Cover Type	Description	Document Type	
1	Technical	Technical Specification, Tender Document, Schedule of Requirement and Compliance, Bidders Information/Indian Agent Information, PAC, Declaration of Local Content etc.	.pdf	
2	Financial	Financial Bid	.pdf	

### Two Bid System:

- The two-bid system will be followed for this tender. In this system bidder must submit their offer in separate sealed envelopes as – Technical Bid and Financial Bid.
- Separate technical bid and financial bid envelopes should be clearly marked as "Envelope No. 1 Technical Bid" and "Envelope No. 2 Financial Bid".
- Both these sealed covers are to be put in a bigger cover which should also be sealed and duly super scribed with our Tender No. & Due Date and to be submitted to the concern department/section mentioned in tender document.
- Bids should be forwarded by Bidders under their original memo / letter head inter alia furnishing details like GST number, Bank Details etc. and complete postal & e-mail address of their office.

### Note:

- The technical offer should not contain any price information. If the price quoted is submitted in technical bid the tender will be rejected at the sole discretion of IIT Goa.
- Initially Technical Bids will be opened and evaluated by the purchase committee. Financial Bid of only Technically qualified bidders will be opened later.
- Contract/ Purchase Order will be awarded to the lowest bidder(L1) of Financial Bid among them.

Form of Contract	Supply
Bid Validity (Days):	120 days
Period of Work/Delivery Period (Days):	45 days

Pre-Bid Meeting Date & Time:	Will be decided on request
Pre-Bid Meeting Place & Address:	N/A
	A prospective bidder who requires clarification regarding the contents of the bidding documents shall notify to the Buyer in writing about the clarifications sought not later than 7 (Seven) days prior to the date of opening of the Bids. Copies of the query and clarification by the purchaser will be sent to all prospective bidders who have participated the bidding documents.
Clarification regarding contents of the tender document/RFP:	A bidder may modify or withdraw his bid after submission provided that the written notice of modification or withdrawal is received by the Buyer prior to deadline prescribed for submission of bids. A withdrawal notice may be sent by email but it should be followed by a signed confirmation copy to be sent by post and such signed confirmation should reach the purchaser not later than the deadline for submission of bids. No bid shall be modified after the deadline for submission of bids. No bid may be withdrawn in the interval between the deadline for submission of bids and expiration of the period of bid validity specified. Withdrawal of a bid during this period will result in Bidder's forfeiture of bid security.
Rejection of bids:	Canvassing by the Bidder in any form, unsolicited letter and post-tender correction may invoke summary rejection with forfeiture of EMD. Conditional tenders will be rejected.
Unwillingness to quote:	Bidders unwilling to quote should ensure that intimation to this effect reaches before the due date and time of opening of the Bid, failing which the defaulting Bidder may be delisted for the given range of items as mentioned in this RFP.
Contract Type:	Tender
Delivery Location:	Indian Institute of Technology Goa Goa Engineering College Campus, BhausahebBandodkar Technical Education Complex, Veling, Farmagudi, Ponda, Goa
Pin Code:	403401
Bid Submission End Date/Date & Time Submission:	12.03.2021 at 17:00hrs
Place of Submission of Bid:	Stores & Purchase Department, IIT Goa, Admin Block, At GEC Campus, Farmagudi, Ponda, Goa-403401
Bid Opening Date & Time:	15.03.2021 at 15:00 hrs
Bid Opening Place:	IIT Goa, Admin Block, At GEC Campus, Farmagudi, Ponda, Goa-403401
Other Terms & Conditions:	As mentioned in technical specification

	Name:Prof. Sachin Kore School of Mechanical Sciences IIT Goa
Technical Clarification:	Email: sachin@iitgoa.ac.in
Tender Inviting Authority:	Name: Assistant Registrar (S&P) Address: Stores& Purchase Department, Email: ar_sp@iitgoa.ac.in
	IIT Goa, Admin Block, At GEC Campus, Farmagudi, Ponda, Goa - 403401
Signing Authority:	Assistant Registrar (S&P)

# भारतीय प्रौद्योगिकी संस्थान, गोवा गोवा अभियांत्रिकी महाविद्यालय परिसर, फारमागुडी, फोण्डा - ४०३४०१, गोवा

# Indian Institute of Technology Goa

Goa College of Engineering Campus, Farmagudi, Ponda - 403401, Goa



#### Part II: Instructions to Bidders

- Schedule of Requirements List of items are attached as Annexure 'A'
- 2. **Technical Details**: Technical details are attached in **Annexure 'B'**
- 3. **Two-Bid System:** In respect of Two-bid system, Bidders are required to furnish clause by clause compliance of specifications bringing out clearly the deviations from specification, if any.
- i) The Bidders are advised to submit the following documents along with Technical Bid
  - a) Compliance certificate in the following format;

Para of tender enquiry specification item-wise (As per annexure B)	Specification of Item offered	Compliance – whether YES/NO	In case of non- compliance, deviation to be specified in unambiguous terms

The offers must strictly be as per the specifications given in Annexure-A. At the same time, it must be kept in mind that mere copying of our specifications in the quotation shall not make the technical bid eligible for consideration. A bid has to be supported with original catalogue (not of photo copy) of the quoted model duly signed by the OEM and the same must be sent along with the technical bid. The quoted model should not become obsolete for a minimum period of 5 years (This is for the availability of spares). Therefore, the model quoted should invariably be highlighted in the leaflet/literature enclosed with the quotation. Noncompliance with above shall be treated as incomplete/ambiguous and the bid may be ignored without giving an opportunity to the bidder for further clarification/negotiation etc.

- b) Bidders Information (Annexure C).
- c) A copy of Indian Agent Agreement / Authorization letter from OEM / OEMs along with tender to be submitted by All Indian Agents, if the manufacturer/supplier is based in abroad.
- d) GST and PAN details
- e) The Bidder should provide a list of customers of previous supply of a similar/ same range of equipment to IIT's/NIT's/Universities with contact details.
- f) It is mandatory for bidders to quote items having Local Content more than 20%. Refer revised Public Procurement (Preference to Make in India), Order 2017 P- 45021/2/2017 B. E. II dated 04.06.20 issued by DPIIT, Ministry of Commerce and Industry, Govt. of India. (Annexure F)
- ii) The following documents should be submitted along with Financial Bid
  - a)Price Bid. (Annexure D)
  - b)Previous order of supplies/Justification of quoted rates. (Annexure E)
- 4. **Delivery Period** supply to be made within <u>45 days</u> from the effective date of issuance of Purchase Order. Please note that P.O. can be cancelled unilaterally by the Institute in case items are not received within the delivery period. Extension of delivery period will be at the sole discretion of the Institute, with applicability of LD clause.
- 5. **Delivery and Transportation** Place for supply / installation is 'Indian Institute of Technology Goa, Ponda Goa'. The transportation cost & Insurance charges up to the destination is to be borne by the bidder.

#### Part III: Conditions of Contract

#### 1. Award of Contract:

- i. Bidders should compulsorily quote for all the items and not for any item mentioned in the tender enquiry.
- ii. IIT Goa shall award the contract to the technically qualified eligible BIDDER whose bid has been determined as the lowest evaluated financial bid.
- iii. If more than one BIDDER happens to quote the same lowest price, IIT Goa reserves the right to award the contract to more than one BIDDER or any BIDDER.

#### 2. Prices:

- a) It is mandatory to quote prices in INR F.O.R., IIT Goa basis only.
- b) In case of Multiple options of the same product, bidders are requested to quote only one best option and not multiple options.
- c) The supplier shall pay and bear all other liabilities, taxes and duties not specifically agreed by the Purchaser in the contract.

#### Pre-installation:

i. Please also mention the pre-installation requirements for the equipment like ambient temperature, humidity, civil work, weather specifications, power specifications, etc. When items are provided full performance satisfaction should be demonstrated.

#### 4. Installation:

- Supplier shall be responsible for installation / demonstration wherever applicable and for after sales service during the warranty period and thereafter as mentioned in the contract.
- ii. Installation / demonstration to be arranged by the supplier free of cost and the same is to be done within 15 days of the arrival of the equipment at site.

### 5. Training:

- i. The supplier shall submit training proposal for the operation and maintenance to the personnel of IIT Goa on the offered equipment/machinery.
- ii. Wherever needed, our technical persons should be trained by the supplier at the project site free of cost. In case the person is to be trained at supplier's site abroad or in India it should be mentioned in the quotation clearly. The supplier should bear all the expenses for such training including 'to & fro' fares and lodging & boarding charges.

#### 6. Terms of Payment:

i. 100% within 30 days after the successful delivery and installation of items at IIT Goa

## 7. Legal Matter:

i. All disputes are subject to Goa jurisdiction only.

#### 8. Rights to Accept, Reject, Amend, Modify:

i. The basic eligibility conditions and conditions of contract are broad guidelines for pre-qualification and the Director, IIT Goa hereby reserves the right to relax / alter / modify / add/delete any or all the conditions without notice.

#### 9. Rights to Accept, Reject Bids:

i. The Director, IIT Goa reserves the right to accept or reject any or all bids without assigning any reason in public interest.

### 10. Penalty/ Liquidated Damages:

- i. Timely delivery is essence of the contract and hence if any consignment be delayed, liquidated damages at the rate 0.5% of the price of the delayed consignment, for each week or part whereof shall be levied and recovered subject to maximum of 10% of total purchase order value.
- ii. IIT Goa reserves the right to cancel the order in case the delay is more than 6 weeks. Penalties if any will be recovered by forfeiting PBG at vendor's cost and risks.

## 11. Supervision of Erection and Commissioning:

i. Successful BIDDER shall depute concerned specialist, for supervision of erection & commissioning of the machine to be carried out. The successful BIDDER shall make necessary arrangement at their own expenses for stay, transport and other expenses of their Specialist during their stay in Goa which also includes imparting free of cost training to IIT Goa personnel.

#### 12. Performance Guarantee (GFR 2017 Rule 171):

- i. Performance Guarantee Bond is mandatory.
- ii. Successful tenderer/ bidder should submit performance guarantee as prescribed above to be sent to The Assistant Registrar, Stores & Purchase Department, IIT Goa on or before 15 days from the due date of issue of order acknowledgement. The PBG to be furnished in the form of bank guarantee as per proforma or annexure of the tender documents, for an amount covering 3 % of the purchase order value.
- iii. The Performance Guarantee should be established in favour of "The Registrar, IIT Goa".
- iv. PBG to be established through any of the National Banks (whether situated at Goa or outstation) with a clause to enforced the same on their local branch of Goa or any scheduled bank (other than national bank) situated at Goa. Bonds issued by co-operative banks will not be accepted.
- v. Performance Guarantee Bond shall be for the due and faithfully performance of the contract and shall remain binding, notwithstanding such variations, alterations for extensions of time as may be made, given, conceded or agreed to between the successful tenderer and the purchaser under the terms & conditions of acceptance to the tender.
- vi. The successful tenderer is entirely responsible for due performance of the contract in letter and spirit and all other documents referred to in the acceptance of tenders.
- vii. The PBG shall be kept valid during the period of contract and shall continue to be enforceable for a period of one year/two years (as mentioned in the tender document) or up to warranty period, plus 60 days whichever is later from the date of order acknowledge. In case PBG needs extensions up to warranty period then supplier shall initiate extensions to PBG one month prior to expiry of PBG.
- viii. For successful suppliers, if PBG is not submitted within 15 days from the date of Order Acknowledgement, then the Purchase Order will be cancelled with forfeiting of EMD.
- ix. No interest shall be payable by the buyer to the Bidder on PBG.

## Annexure - A

# List of items required

SI. No.	Description of Items	Qty
1	Advanced Phased Array Ultrasonic Flaw Detector with Accessories	01
2	Ultrasonic Thickness Gauge with Accessories	01
3	Eddy Current Flaw Detector with Accessories	01

## **Technical Specification for Non-destructive Testing Equipment**

- 1. Ultrasonic Phased Array TOFD Machine
- 2. Accessories of Ultrasonic Phased Array TOFD Machine
- 3. Ultrasonic thickness gauge
- 4. Accessories of Ultrasonic thickness gauge
- 5. Eddy Current Flaw Detector
- 6. Accessories of Eddy Current Flaw Detector

All items to be quoted in a single quotation as bundle price. Individual items will not be considered.

S. No.	Paramet	er	Specified Value	Offered values/ Confirmation
1.1.	Phased A	Array / Element detection Ch	annel	
	1.1.1.	Channels	Minimum 16	
	1.1.2.	Aperture	≥ 16	
	1.1.3.	Number of elements	≥ 64	
	1.1.4.	Group quantity of probing system	2 groups (PA, UT, or TFM) or 2PA + 1 UT.	
	1.1.5.	Segments in angular section (Focal laws )	≥ 1024	
	1.1.6.	Focal law	≥ 8 beam set up and ≥ 1000 focal laws	
	1.1.7.	Scan Plan	Onboard Scan Plant tool for Phased Array and TFM/FMC	
	1.1.8.	Scanning	Single, Linear, Sectorial compound and TFM / FMC with (A-Scan. B-scan, C-scan and S-scan)	
1.2.	Phased A	Array Pulser	,	
	1.2.1.	Pulse Rate Frequency (PRF)	≥ 12kHz	
	1.2.2.	Pulse Shape	Negative Suqare Wave	
	1.2.3.	Pulse width	PA channel : ≤ 30ns - 500ns or higher range UT (ToFD) Channels : ≤ 50ns - 1000 ns or higher range	
	1.2.4.	Fall time	≤ 10 ns	
	1.2.5.	Pulse Width Resolution	≤ 2.5 ns	
	1.2.6.	Pulse Voltage	PA channels: 40V, 80V & 115V or more setting. UT channels: 95V, 175V, 295 Volts or more setting.	
1.3.	Phased A	Array Receiver and Digitizer		
	1.3.1.	Receiver Gain	PA channel: ≥ 80 dB or better range. UT (ToFD) channel: ≥ 120 dB or better range.	
	1.3.2.	Receiver Input /output impedance	PA channels : $\geq 50\Omega / 100\Omega$ pulse echo and catch UT (ToFD) channels : $\geq 50\Omega / 50\Omega$ echo and receive	
	1.3.3. Receiver Band width range		PA channel: 0.5 MHz to 18 MHz or more range UT (ToFD) channel: 0.5 MHz to 25 MHz or more range	
	1.3.4.	Slope	Minimum 40 dB/ µs	
	1.3.5.	Rectification	Positive HW, Negative HW, Full, RF	
	1.3.6.	Digitizing frequency	≥100 MHz	

		T =	T	
	1.3.7.	Display refresh rate	A-Scan 60 Hz & S-Scan 20Hz to 30Hz,	
			For Volume Corrected S-scan 30hz	
	<del>1.3.8.</del> —	- A-Scan Height	Up to 800%	
	1.3.9.	Real Time Averaging	PA: 2, 4, 8, 16 UT: 2, 4, 8, 16, 32, 64	
	1.3.10.	Filter	PA channel: 3 low-pass, 6 band-pass,	
			and 4 highpass filters UT channel: 8	
			low-pass, 6 band-pass, and 4	
			highpass filters (3 low-pass filters	
			when configured in TOFD) & Special	
	1 2 11	TCC	Video filters for smoothing of signal	
	1.3.11.	TCG	No. Of Points:32	
	1.3.12.	A-scan data points	Up to 16384	
1.4.	Environn		T	
	1.4.1.	Operating Temperature	0°C to 45 °C or more range	
		range		
	1.4.2.	Storage Temperature range	-20°C to 60 °C or more range	
	1.4.3.	Shock	4' transit drop to MIL-STD-810G	
			516.6	
	1.4.4.	Ingress protection (IP)	IP 65 or better	
		rating		
1.5.	Safety c	ase provisions for the instrur	ment and operation	
1.5.	1.5.1.	Shock and water resistant cas	-	
	1.5.2.		eparate stand to handle the instrument	
			ner for operation and measurements	
		independently		
	1.5.3.	Carrying case for safe transpo	ort.	
1.6.	Power si	upply		
	1.6.1.	Battery	Two Re-chargeable Li-ion battery of	
	1.0.1.	Battery	suitable rating for continuous	
			operation with hot swap $\geq 5$ hours.	
			Capacity $\geq$ 93 Wh (x 2)	
	1.6.2.	Dattam/ sharear		
	1.0.2.	Battery charger	Rechargeable battery charger suitable	
			for above battery ratting, operated by	
	1.6.2		100 to 240 VAC, 50 HZ,	
	1.6.3.	Power supply	Suitable for operation of equipment in	
			wall plug condition. Operated by 100	
			to 240 VAC, 50 HZ	
	1.6.4.	Compliance	Meets IATA air transport regulations	
			with one contained installed battery	
			and one packed external battery.	
1.7.	Weight &	Dimenstion	≤6.5 kg along with battery 335 mm ×	
			221 mm × 151 mm	
1.8.	Data visi	ualization and transfer		
	1.8.1.	User Interface software	Customised with UT software, Third	
			party programs can connect to the	
			operating software, so that the data	
			can be accessed with analysis	
			programs.	
	1.8.2.	Instructional Material		
	1.8.2.	Instructional Material	Rich text, JPG, PNG, BMP, PDF or	
	1.0.0	-	Video (MP4)	
	1.8.3.	Zoom	Any data view may be expandable to	
		1.0	full screen with gesture on other OSC.	
	1.8.4.	Views	A-Scan, B-Scan, C-Scan overview, E-	
			Scan, S-Scan	
	1.8.5.	Probe selector	Swap between conventional, focus	
			and phased array on same screen	
	1.8.6.	Evaluation	3 gates, one can be used as interface	
			echo gate	
	1.8.7.	Measurements	Amplitude, Depth, Distance, % Wall	
			Loss, Thinnest point, X and Y position	
	1.8.8.	Amplitude Calibration	Phased array: TCG (Time correction	
			gain), ACG (Amplitude correction	
			gain) Material velocity, wedge Delay,	
	1	1	1 Janis Laterial Felocity, Wedge Deldy,	

1.8.9. Axes information   Minimum 2 axis encoder (digital quadrature encoders for X-Y axes).			T		1
1.8.9. Axes information Minimum 2 axis encoder (digital quadrature encoders for X-Y axes).  1.8.10. Calibration certification EN ISO 18563-1 for PA EN ISO 1868-1 for UT (ToFD)  1.8.11. Alarm Audio or visual alarm  1.9. Connectivity  1.9.1. Wi-Fi 80.2.11 b. g. n 1.9.2. Connectors USB 2.0, USB 3.0, Ethernet, HDMI 1.9.3. Remote data analysis Local Network and internet- Enabled via inspection works connected.  1.9.4. Inspection Works Enabled  1.9.4. Hard drive capacity ≥ 64 GB 2 8GB DDR (RAM)  1.10.1. Hard drive capacity ≥ 64 GB 2 8GB DDR (RAM)  1.10.2. Data Capture Full A-Scan capture for every C-Scan points, all settings, Recall on instruments with full analysis capability.  1.10.3. Setting files All instruments settings plus positive ion work flow 1.10.4. Screen capture JPG format 1.10.5. Report PDF format  1.10.6. Application software Application Software for UT Data acquisition and post processing for flaw characterization  1.11. Display (TFT LCD)  1.11.1. Size 264 mm (10.4") diagonal or larger in size 1.11.2. Resolution 1024 x 768 pixels or better 1.11.3. Mode Indoor and Outdoor specific colour mode 1.11.4. Viewing angle ± 85° in all direction 1.11.5. Gloved Operation Yes (Touch screen) 1.11.6. Surface Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12. Acceptance criteria  1.12. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser's report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				Encoder calculator, dead elements check.	
I.8.11. Alarm   Audio or visual alarm		1.8.9.	Axes information	Minimum 2 axis encoder (digital	
1.9.   Connectivity   1.9.1.   Wi-Fi   802.11 b. g. n     1.9.2.   Connectors   USB 2.0, USB 3.0, Ethernet, HDMI     1.9.3.   Remote data analysis   Local Network and internet- Enabled via inspection works connected.     1.9.4.   Inspection Works   Enabled     1.10.   Data Storage, Application software     1.10.1.   Hard drive capacity   ≥ 64 GB   ≥ 8GB DDR (RAM)     1.10.2.   Data Capture   Full A-Scan capture for every C-Scan points, all settings, Recall on instruments with full analysis capability.     1.10.3.   Setting files   All instruments settings plus positive ion work flow     1.10.4.   Screen capture   JPG format     1.10.5.   Report   PDF format     1.10.6.   Application software   Application Software for UT Data acquisition and post processing for flaw characterization     1.11.   Display (TFT LCD)     1.11.1.   Size   264 mm (10.4") diagonal or larger in size     1.11.2.   Resolution   1024 × 768 pixels or better     1.11.3.   Mode   Indoor and Outdoor specific colour mode     1.11.4.   Viewing angle   ± 85° in all direction     1.11.5.   Gloved Operation   Yes (Touch screen)     1.11.6.   Surface   Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display     1.12.   Acceptance criteria     1.12.1.   Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.     1.12.2.   Calibration of equipment using 150 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)     1.12.3.   Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.			Calibration certification	EN ISO 12668-1 for UT (ToFD)	
1.9.1. Wi-Fi 1.9.2. Connectors 1.9.3. Remote data analysis 1.9.4. Inspection Works 1.9.4. Inspection Works 1.9.4. Inspection Works 1.10.1 Data Storage, Application software 1.10.1. Data Capture 1.10.2. Data Capture 1.10.3. Setting files 1.10.4. Screen capture 1.10.5. Report 1.10.6. Application software 1.10.7. Application software 1.10.8. Serven capture 1.10.9. Display (TFT LCD) 1.11.1. Size 1.11.2. Resolution 1.11.3. Mode 1.11.4. Viewing angle 1.11.5. Gloved Operation 1.11.6. Surface 1.11.6. Surface 1.11.7. Calibration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications block. (PA:- EN ISO 12668-1) 1.12.3. Supply of user's manual of the instrument that includes safety instrument using ISO 19675 calibration block. (PA:- EN ISO 12668-1) 1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.			-	Audio or visual alarm	
1.9.2.   Connectors   USB 2.0, USB 3.0, Ethernet, HDMI	1.9.		-		
1.9.3. Remote data analysis Local Network and internet- Enabled via inspection works connected.  1.9.4. Inspection Works Enabled  1.10. Data Storage, Application software  1.10.1. Hard drive capacity ≥ 64 GB ≥ 8GB DDR (RAM)  1.10.2. Data Capture Full A-Scan capture for every C-Scan points, all settings, Recall on instruments with full analysis capability.  1.10.3. Setting files All instruments settings plus positive ion work flow  1.10.4. Screen capture JPG format  1.10.5. Report PDF format  1.10.6. Application software Application Software for UT Data acquisition and post processing for flaw characterization  1.11. Size 264 mm (10.4") diagonal or larger in size  1.11.2. Resolution 1024 x 768 pixels or better  1.11.3. Mode Indoor and Outdoor specific colour mode  1.11.4. Viewing angle ± 85° in all direction  1.11.5. Gloved Operation Yes (Touch screen)  1.11.6. Surface Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				_	
1.9.4. Inspection Works   Enabled					
1.10. Data Storage, Application software  1.10.1. Hard drive capacity ≥ 64 GB ≥ 8GB DDR (RAM)  1.10.2. Data Capture Full A-Scan capture for every C-Scan points, all settings, Recall on instruments with full analysis capability.  1.10.3. Setting files All instruments settings plus positive ion work flow  1.10.4. Screen capture JPG format  1.10.5. Report PDF format  1.10.6. Application software Application Software for UT Data acquisition and post processing for flaw characterization  1.11. Display (TFT LCD)  1.11.1. Size 264 mm (10.4") diagonal or larger in size  1.11.2. Resolution 1024 x 768 pixels or better  1.11.3. Mode Indoor and Outdoor specific colour mode  1.11.4. Viewing angle ± 85° in all direction  1.11.5. Gloved Operation Yes (Touch screen)  1.11.6. Surface Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment unsing ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.			,	via inspection works connected.	
1.10.1. Hard drive capacity    2 64 GB     8 8GB DDR (RAM)     1.10.2. Data Capture   Full A-Scan capture for every C-Scan points, all settings, Recall on instruments with full analysis capability.   1.10.3. Setting files   All instruments settings plus positive ion work flow     1.10.4. Screen capture   JPG format     1.10.5. Report   PDF format     1.10.6. Application software   Application Software for UT Data acquisition and post processing for flaw characterization     1.11. Size   264 mm (10.4") diagonal or larger in size     1.11.1. Size   264 mm (10.4") diagonal or larger in size     1.11.2. Resolution   1024 x 768 pixels or better     1.11.3. Mode   Indoor and Outdoor specific colour mode     1.11.4. Viewing angle   ± 85° in all direction     1.11.5. Gloved Operation   Yes (Touch screen)     1.11.6. Surface   Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display     1.12. Acceptance criteria     1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.     1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)     1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				Enabled	
2 8GB DDR (RAM)	1.10.				
Display (TFT LCD)   1.11.2.   Resolution   Resolution			, ,	≥ 8GB DDR (RAM)	
ion work flow   1.10.4.   Screen capture   JPG format   1.10.5.   Report   PDF format     1.10.6.   Application software   Application Software for UT Data acquisition and post processing for flaw characterization   1.11.   Display (TFT LCD)     1.11.1.   Size   264 mm (10.4") diagonal or larger in size   1.11.2.   Resolution   1024 x 768 pixels or better   1.11.3.   Mode   Indoor and Outdoor specific colour mode   1.11.4.   Viewing angle   ± 85° in all direction   1.11.5.   Gloved Operation   Yes (Touch screen)     1.11.6.   Surface   Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display   1.12.1.   Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.   1.12.2.   Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 12668-1)   1.12.3.   Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.		1.10.2.	Data Capture	points, all settings, Recall on instruments with full analysis capability.	
1.10.5. Report PDF format  1.10.6. Application software Application Software for UT Data acquisition and post processing for flaw characterization  1.11. Display (TFT LCD)  1.11.1. Size 264 mm (10.4") diagonal or larger in size 264 mm (10.4") diagonal or larger in size 1.11.2. Resolution 1024 x 768 pixels or better 1.11.3. Mode Indoor and Outdoor specific colour mode 1.11.4. Viewing angle ± 85° in all direction 1.11.5. Gloved Operation Yes (Touch screen)  1.11.6. Surface Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria 1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				ion work flow	
1.10.6. Application software  Application Software for UT Data acquisition and post processing for flaw characterization  1.11. Display (TFT LCD)  1.11.1. Size  264 mm (10.4") diagonal or larger in size  1.11.2. Resolution  1024 x 768 pixels or better  1.11.3. Mode  Indoor and Outdoor specific colour mode  1.11.4. Viewing angle  1.11.5. Gloved Operation  Yes (Touch screen)  1.11.6. Surface  Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.			· ·		
1.11. Display (TFT LCD)  1.11.1 Size  264 mm (10.4") diagonal or larger in size  1.11.2 Resolution  1.11.3 Mode  1.11.4 Viewing angle  1.11.5 Gloved Operation  1.11.6 Surface  1.11.6 Surface  1.11.7 Acceptance criteria  1.12.1 Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser, report generation, data transfer to computer etc.  1.12.2 Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3 Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.		1.10.5.	Report		
1.11.1. Size  264 mm (10.4") diagonal or larger in size  1.11.2. Resolution  1024 x 768 pixels or better  1.11.3. Mode  Indoor and Outdoor specific colour mode  1.11.4. Viewing angle  1.11.5. Gloved Operation  1.11.6. Surface  Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.		1.10.6.	Application software	acquisition and post processing for	
1.11.2. Resolution  1.11.3. Mode  1.11.4. Viewing angle  1.11.5. Gloved Operation  1.11.6. Surface  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.	1.11.	Display (	TFT LCD)		
1.11.3. Mode  Indoor and Outdoor specific colour mode  1.11.4. Viewing angle  1.11.5. Gloved Operation  1.11.6. Surface  Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				size	
mode   1.11.4. Viewing angle   ± 85° in all direction   1.11.5. Gloved Operation   Yes (Touch screen)   1.11.6. Surface   Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display   1.12.   Acceptance criteria   1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.   1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)   1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				-	
1.11.5. Gloved Operation Yes (Touch screen)  1.11.6. Surface Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				mode	
1.11.6. Surface Chemically strengthened glass, scratch resistance, chemical resistant, optically bonded to display  1.12. Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.					
scratch resistance, chemical resistant, optically bonded to display  1.12.  Acceptance criteria  1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.				,	
1.12.1 Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.  1.12.2 Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3 Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.		1.11.6.	Surface	scratch resistance, chemical resistant,	
<ul> <li>1.12.1. Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser, report generation, data transfer to computer etc.</li> <li>1.12.2. Calibration of equipment using ISO 19675 calibration block. (PA:- EN ISO 18563-1 and UT:- EN ISO 12668-1)</li> <li>1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.</li> </ul>	1.12.	Acceptar	nce criteria	Toperedity behave to display	
ISO 18563-1 and UT:- EN ISO 12668-1)  1.12.3. Supply of user's manual of the instrument that includes safety instructions during operation and maintenance of the instrument.			Demonstration of full functionality of the Phased Array Ultrasonic flaw detector as per the technical specifications at the purchaser's site including analysis of standard sample set provided by the purchaser,		
instructions during operation and maintenance of the instrument.		1.12.2.	. Calibration of equipment using ISO 19675 calibration block. (PA:- EN		
1.12.4. Completion of specified training along with certification.			Supply of user's manual of instructions during operation		
		1.12.4.			

## 2.0 Required Accessories of Ultrasonic Phased Array TOFD Machine

S. No.	Name/Specification	Specified Value		Offered values/ Confirmation
2.1	PA Probe	5 MHz,32 elements with 32X10mm	One No.	

		active aperture and 5mtr cable length	
2.2	Angle beam Wedges for PA probe	Angle beam wedge with 55degree refracted angle for shear wave in steel with 40 to 70 degree beam sweep.	One No.
2.3	Odegree beam Wedges for PA Probe	Odegree longitudinal wave in steel for corrosion or lamination inspection	One No.
2.4	PA Probe	5 MHz,16 elements with 9.6X10mm active aperature and 5mtr cable length	One No.
2.5	Angle beam Wedges for PA probe	Angle beam wedge with 55degree refracted angle for shear wave in steel with 40 tp 70 degree beam sweep.	One No.
2.6	Scanner	Manual Scanner with four magnetic wheel and copacity of handling one pa probe and One Tofd pair at a time	
2.7	TOFD Probe	10Mhz, 6mm dia probe 5MHz , 6mm dia probe 2.25MHz , 6mm dia probe	Two Nos each.
2.8	Wedges for TOFD Probe	TOFD wedges with 70 degree, 60 degree and 45 degree reftracted angle in steel with longitudinal waves	Two Nos each.
2.9	Scanner	Hand Scanner for TOFD weld inspection on flat plates, pipes, and curved surfaces. One encoded axis. Kit includes one TOFD Hand Scanner frame, one wheel encoder and 2.5mtr TOFD Cables.	One No.
2.10	Encoder	Encoder compatible with equipment to measure scanning length	One No.
2.10	One battery	One Spare battery	One No.
2.12	Standard Block	One CS CalibrationV1 Block	One No.
3	ULTRASONIC THICKNESS		One No.
3.1	System Capability-	Dual and Single element transducer compatibility, echo to echo, coating thickness,	
3.2	Thickness range, Suitability-	For all classes of materials (polymers, metals, ceramics, composites,	

		elastomers)		
3.3	Transducer Frequency range-	2 to 30 MHz		
3.4	Operational Temperature range-	0 "C to 45 °C.		
3.5	Material Velocity range (mm/ps),	0.5 to 18,		
3.6	Device- t,	Hand held device tested for vibration, shock and impact		
3.7	Power requirement-	Battery operated		
3.8	Operational control of all parameters ,	Full operational control		
3.9	Display	Color display for better viewing indoors and outdoors		
3.10	, Data transfer:	SD Card and USB		
3.11	Capability	data logging, echo-to-echo measurement, and single element measurement and A scan		
4	ESSENTIAL ACCESSORIES of ULTRASONIC THICKNESS GAUGE			
4.1	Block samples for Thickness gauging: for instrument verification	Material Mild Steel,Carbon Steel ,Stainless Steel	One No. each	
4.2	Carrying Case	Case for better handling of the hand held device	One No.	
4.3	System Compliance.	IP67	One No.	
4.4	Dual element transducer	(5MHz,) connector with cables , Thickness range: I mm to 18 mm in steel.	One No.	
4.5	Dual element transducer for surface coating measurement.	7.5MHz	One No.	
5	Eddy current Equipment:-		One No.	
5.1	Capability	Flaw detection, conductivity and coating thickness measurement, surface inspection, weld inspection		
5.2	. Compliance	IP66 and EN-		

		15548		
5.3	Frequency Capacity-	8 -12 MHz		
5.4	Gain-	1 dB to 90 dB,		
5.5	Rotation-	O ° to 350°		
5.6	Connectors-	Twoprobe (16 way Universal connector and a BNC connector),		
5.7	Inputs and Outputs-	USB. VGA. I5pin I/O. analog outputs.		
5.8	Compatible Probe Types	Absolute and differential, Bridge/reflection configuration,		
5.9	Operational Temperature range-	O °C to 45 °C,		
5.10	Device :	Hand held device tested for vibration, shock and impact		
5.11	Power and Filters :	BatterY operated, Filters- Lowpass,wide band. High -pass,		
5.12	Operational Control-	Full software control of allparameters		
5.13	Display and Data Transfer : ,	Color disPlaY for better viewing indoors and outdoors, Data transfer: SD Card and USB		
6	ESSENTIAL ACCESSORIES OF Eddy Current Flaw Detector			
6.1	Conductivity Probe:	Frequency 60 kHz or better	One No.	
6.2	Surface reference standards,	Material- Mild Steel Material-Carbon Steel Material- Stainless Steel Material- Aluminium Steel	One No.each	
6,3	Absolute probes	frequency 500kHz to 1 MHz	One No.	
6.4	Certified conductivity reference standards ,	Conductivity reference standard	One No.	

# (To be printed on letterhead of the bidder)

# Annexure - C

## **Bidders Information**

1.	Name of the Bidder	
2.	Address of the Bidder	
3.	PAN No.	
4.	GSTN No.	
5.	State of GST Registration	
6.	E-mail	
7.	Contact Person's Name & Designation	
8.	Mobile No.	

## (To be printed on letterhead of the bidder)

## Annexure - D

## **PRICE BID FORMAT**

S.No.	Item description & short specification	HSN Code/SAC Code	Qty in Units	GST %	Price Basis	Total Bid Price
1.	Advanced Phased Array Ultrasonic Flaw Detector with Accessories					
2.	Ultrasonic Thickness Gauge with Accessories					
3.	Eddy Current Flaw Detector with Accessories					
4.	Installation and Commissioning Charges (if any, quote in INR)					
5.	Agency Commission (if any, quote in %)					
6.	Other Charges (if any, please specify)					
Grand	Total				•	

#HSN Code: "Harmonized System of Nomenclature Code No." and SAC Code: "Service Accounting Codes Code No."

- 1. Delivery Mode: Delivery at IIT Goa, at site only.
- 2. Terms of payment: 100% payment within 30 days after the successful delivery and installation of the item at IIT Goa.
- 3. Validity of the bid: 120 days from the date of submission of quotation/tender.

	Signature Name		
Place:	Company Name & Address:		
Date:	Affix Rubber Stamp:		

Note: Price Bid should be submitted in given format only. For additional information/extra items above format may be typed and used.

## Reasonability of Prices

Please quote best minimum prices applicable for a premier Educational and Research Institution. The party must give details of at least two purchase orders identical or similar equipment, supplied to any IITS/Research Institutions/ other organisation as per below Format (to be enclosed in Financial Bid) along with the final price paid and details are mandatory.

# **Previous Supply Orders**

Name of the Firm \_\_\_\_\_

S.No.	РО	Description &	Value	Date of	Remarks	Has the	Contact
	No.	Quantity of	of	completion of	indicating	equipment	Person
	&	ordered	Order	delivery as per	reasons for	being	along with
	Date	equipment		contract	late delivery, if any and	installed	Telephone
					justification of	satisfactorily (attach a	no., Fax No. and e-
					price	certificate	mail
					difference of	from the	address
					their supply	Purchaser/	
					order & those	Consigner)	
					quoted to us		
L	I	<u> </u>	I	<u> </u>	<u> </u>	<u>I</u>	I.

Place: \_\_\_\_\_
Date:

Signature and Seal of the Manufacturer / Bidder

## **DECLARATION OF LOCAL CONTENT**

(To be given on company letter head - For tender value below Rs.10 crores)
(To be given by Statutory Auditor/Cost Auditor/Cost Accountant/CA for tender value above Rs.10 crores)

	Date:
To, The Registrar, Indian Institute of Technology Goa, At GEC Campus, Farmagudi, Ponda - Goa	
Sub: Declaration of Local content	
Tender Reference No:	
Name of Tender: -	
Country of Origin of Goods being offered: We hereby declare that an item offered has % local content	
"Local Content" means the amount of value added in India which sha the item being offered minus the value of the imported content in customs duties) as a proportion of the total value, in percent.	
"*False declaration will be in breach of Code of Integrity under R General Financial Rules for which a bidder or its successors can be years as per Rule 151 (iii) of the General Financial Rules along with may be permissible under law."	debarred for up to two
Yours faithfully, (Signature of the Bidder, with Official Seal)	

## FORMAT FOR PERFORMANCE GUARANTEE BOND

(To be typed on Non-judicial stamp paper of the value of Indian Rupees of One Hundred) (TO BE ESTABLISHED THROUGH ANY OF THENATIONAL BANKS (WHETHER SITUATED AT GOA OR OUTSTATION) WITH A CLAUSE TO ENFORCE THE SAME ON THEIR LOCAL BRANCH AT GOA OR ANY SCHEDULED BANK SITUATED AT GOA. BONDS ISSUED BY CO-OPERATIVE BANKS ARE NOT ACCEPTED.

To, The Registrar, Indian Institute of Technology, Goa Farmagudi, Ponda, Goa – 403401

## **LETTER OF GUARANTEE**

Tender AND	WHEREAS Indian Institute of Technology, Goa (Buyer) have invited Tenders vide No
WHER wishing irrevoc <b>Techn</b> percen which	EAS the said tender document requires that any eligible successful tenderer (seller) g to supply the equipment / machinery, etc. in response thereto shall establish an able Performance Guarantee Bond in favour of "Registrar, Indian Institute of cology, Goa" in the form of Bank Guarantee for Rs
perforr Techno	NOW THIS BANK HEREBY GUARANTEES that in the event of the said tenderer (seller) to abide by any of the conditions referred in tender document / purchase order / mance of the equipment / machinery, etc. this Bank shall pay to Indian Institute of blogy, Goa on demand and without protest or demur Rs
	This Bank further agrees that the decision of Indian Institute of Technology, Goa (Buyer) hether the said Tenderer (Seller) has committed a breach of any of the conditions referred er document / purchase order shall be final and binding.
	We,
Notwi	thstanding anything contained herein:
1.	Our liability under this Bank Guarantee shall not exceed Rs
	(Indian Rupeesonly).
	This Bank Guarantee shall be valid up to(date) and We are liable to pay the guaranteed amount or any part thereof under this bank
ی.	guarantee only and only if IIT Goa serve upon us a written claim or demand on or before
4.	This Bank further agrees that the claims if any, against this Bank Guarantee shall be enforceable at our branch office at situated at
	(Address of local branch).
Date:	Yours truly,
	Signature and seal of the Guarantor:
	Name of Bank: